




NPH**DIN Rail Mount - 3 Phase
to 40 Amps AC @ 40°C Ambient****FEATURES:**

- Standard relays approved to the following: UL, CSA, VDE and CE
- Finger-safe cover standard
- Zero voltage switching standard
- Two or three legs controlled
- Voltage transient protection standard on 3 leg models only


PART NO.	INPUT RANGE	LOAD CURRENT (Amps AC)/pole	LINE VOLTAGE RANGE (VAC)	TRANSIENT OVER VOLTAGE	APPLICATION NOTES
HBC-T50DK	3-32 VDC	0.1 - 30	48 - 530	1200 V _{pik}	• Three legs controlled • Transient protection standard
HBC-T50AK	90-280 VAC				
HBC-90HDK-2	3-32 VDC	0.1 - 40			• Two legs controlled by individual SSRs
HBC-90HAK-2	90-280 VAC				

NOTES:

- 1) Heat sink black anodized aluminum
- 2) All dimensions in inches
- 3) Consult HBCcontrols for application information
- 4) Cover adds approx. 0.4" to assembly height

**NOTES:**

- 1) Heat sink black anodized aluminum
- 2) All dimensions in inches
- 3) Consult NPH Heaters for application information
- 4) Cover adds approx. 0.4" to assembly height

**NPH****National Plastic Heater Sensor & Control Co.**

phone: 416.491.8436 toll free: 1.877.674.9744 fax: 416.491.2433

Toronto, Ontario Canada e-mail: sales@nphheaters.com website www.nphheaters.com